



DESIGN FEATURES

VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of **+/-3°** per gasket
- Covering most common pipe materials



OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- **ANTI-CORROSION**
- Thickness: **Epoxy powder coating of 200-250µm**
- Temperature : **Spraying temperature over 200°C**
Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder: **AkzoNobel**, Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled

APPLICATION SCENARIO



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂

II 工厂CNC

III 工厂

IV 工厂

V 工厂 GB 工厂 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

VI 工厂 / 工厂 / 工厂

Exhibition Photos



Our Certificates



□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□
 □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□
 □□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□□□
 □□□□□□□□□□□□ 2~5 □□□□□□□□□□□□□□□□

□□ MOQ
 □□□□□□□□ 1pc □

□□□□□□□□□□
 □□□□□ 100 □□□□□□□□ 2 □□□□□□□□□□□□□□□□
 □□□□□ TUV □ API □ WRAS □ CE □ ISO □□□□
 □□□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □

□□□□□□□□□□□□□□□□

