

## PRODUCT STRUCTURE

### Features

- Size range DN100-1200mm
- Standard-ISO/ BS/DIN /AWWA/API
- Tests standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel/WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-420/S5431/SS316
- Fusion bonded epoxy coating- Min 300 Microns

This series tilting check valves are suitable to be used at the exit of the pump whose medium is water. It is used to prevent or reduce medium back from water hammer. So it can protect the pipeline system. Suitable temperature  $\leq 80^{\circ}\text{C}$



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# COMPANY FACTORY



## COMPANY INFORMATION



□ 鋼 鋼 : 鋼 鋼 鋼, 鋼 鋼 鋼 鋼.

□ 鋼 CNC 鋼 鋼, 鋼 鋼 鋼, 鋼 鋼 鋼 鋼, 鋼 鋼 鋼 鋼.

□ 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼 鋼.

☒ 鋼 鋼 鋼 鋼 (Houston) 鋼 鋼 鋼 鋼 鋼 鋼.

◆ 鋼 鋼 : GB, 鋼 鋼, 鋼 鋼, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC WRAS, KTW, API 6D, API609.

VI 鋼 鋼 : 鋼 鋼 鋼, 鋼 鋼, 鋼 鋼 鋼, 鋼 鋼, 鋼 鋼 鋼, 鋼 鋼 鋼, 鋼 / 鋼 / 鋼 鋼 鋼, 鋼 鋼.

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

## COMPANY QUALIFICATION



## COMPANY EXHIBITION



**Q :** 100% 100% 100% 100% 100%?

A : 100% 100%, 100%, 100%, 100%, 100% 100%.

**Q :** 100% 100% 100% 100%?

A : 100%, 100%, 100%, 100% 100%. RKSfluid 100% 100% 100%. 100% 100%, 100% 100%.

**Q :** 100% 100% 100% 100%?

A : RKSfluid 100% 100% 100% 100% 4 100% 100% 100%.

**Q :** 100% 100% 100%

A : 100% 100% 2 ~ 5 100% (2 ~ 5 100%) 100%. 100% 100% 100% 100% 100%.

**Q : MOQ.**

A : 100 100% 100 1pc.

**Q :** 100% 100% 100% 100%?

A : 100% 100% 100% 100%, 2 100%. 100% 100% 100%.

100% TUV, API, WRAS, CE, ISO 100% 100%.

100%, DIN, ASME, BS EN, JIS, API, AWWA.

**Q :** 100% 100% 100% 100% 100%?

A : RKSfluid 100% 20 100% 70 100% R & D 100% 100%, 100% 100% 100% 100%.