


Product Display




Product Dimensions


Horizontal Type Pneumatic Butterfly Value



Size	O	G	A	L	H1	H
DN20	78.0	RD44*1/6	66.0	140	89	166.5
DN25	78.0	RD52*1/6	66.0	140	89	166.5
DN32	86.0	RD58*1/6	66.0	140	89	166.5
DN40	90.0	RD65*1/6	70.0	159	105	186.0
DN50	106.0	RD78*1/6	76.0	159	105	192.0
DN65	124.0	RD95*1/6	80.0	159	105	197.0
DN80	139.0	RD110*1/4	84.0	210	122	225.0
DN100	159.0	RD130*1/4	104.0	248	135	260
DN125	185.0	RD160*1/4	130.0	248	135	274.0
DN150	225.0	RD190*1/4	150.0	315	165	330.0



Φ	Size	D2	D1	L	H1	H
Φ 19	3/4"	50.5	16.1	66	205	245
Φ 25	1"	50.5	22.4	66	205	245
Φ 32	1 1/4"	50.5	28.8	66	205	245
Φ 38	1 1/2"	50.5	35.1	66	205	245
Φ 45	1 3/4"	64	42	70	210	250
Φ 51	2"	64	47.8	72	215	255
Φ 57	2 1/4"	77	53	76	220	265
Φ 63	2 1/2"	77	59.5	76	225	265
Φ 76	3"	91	72.2	76	230	285
Φ 89	3 1/2"	106	85	84	235	290
Φ 102	4"	119	97.6	90	240	295



Size	D1	D2	A	H	L
19	16.1	50.5	135	68	66
25.4	22.4	50.5	135	68	66
31.8	28.8	50.5	135	68	66
38.1	35.1	50.5	135	72	66
45	42	64	135	74	70
50.8	47.8	64	135	79	72
57	53	77	135	83	76
63.5	59.5	77	135	86	76
76.2	72.2	91	135	96	76
89	85	106	160	102	84
101.6	97.6	119	160	110	90
108	104	119	160	112	90
114	110	130	160	112	106
133	128	145	210	128	122/108
159	153.5	183	210	147	132/110
219	214	233.5	315	183	134
273	267	286	315	257	142

Application



Dairy

Drink & Beverage

Enzymes



Pharmaceuticals


Daily Necessaries

Cosmetics

Nome dos produtos	Válvula borboleta sanitária de grau de aço inoxidável
Tamanho	DN15-300
Fim da conexão	Soldagem, Grampo, Rosqueado, Flange
Padrão	DIN, SMS, ISO, RJT, 3A, IDF
Selagem	EPDM, Viton, Silicone
Método de Operação	Manual, pneumático, elétrico
Pressão Máxima	10 bar
Temp de trabalho	-10 °C --- + 120 °C
Seleção de alça	Punho completo, multi-posições + punho de plástico, multi-posições + punho de aço inoxidável
Inscrição	Alimentos, bebidas, produtos químicos industriais etc ...



- 2 professional testing centers
- 28 senior professional researchers
- Independent research and development team



- 21 years of professional experience
- 100% high level ex-factory inspection
- 2 years quality assurance, repair and replacement

— RKSfluid —

- China standard reference unit, to participate in the development of the relevant valve industry standards.
- We have created a R&D and service center in Houston, Texas, USA.
- GB, German standard, American standard, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRAS WRC, KTW, API 6D, API 609



Four factories



Partners



Exhibition Photos



Our Certificates





Braçadeira de aço inoxidável de qualidade alimentar Válvula borboleta sanitária Vlave com alça quadrada de 4 posições