□□□:
□□□□□□ □□□□□ □□□□ □□ □□□□□□ □□□□□□ □□□□□□ □□□□□ □□□□ □□□□□ □□□□□ □□□ □□ □□□□□□□ □□□□ □□ □□□□□□
PTFE □□□□□□ □□□□□□ □□□□ □ □□□□□□ PTFE 3 □□□ □□□ □□ □□□ □□□□□□ □□□ □□□ □□ □□□□.□□□□□ □□□□□□ □□□□□
□□□ □□□.□□□□□ □□□□□□□ □□□□□□□ □□□□□□□ □□□□□ □□□ □□□□□□□ □□□□□□□ □□□□ □□□□ □□□□□ □□□ □ □□ 4 □□□
□□□ □□□□□ □□□□□□□□ □□□□□□ □□□□□□ Valve □□□ □ □□□□□□ □□□□□□□□□ □□□□□ PTFE □ Nylon Painting □
□□□ □ □□□□□ □□□□□□□□□ □□□□□□□ □□□□□ □□□□□□□ □□□□□□□□.

□□□□:
1. □□□□□□□□□ □□ □□ □□ □□□□□□ □□ □□□□□□ □□□ □□□
□□□□□□ □□□□□□ □□□□ □□□□□□□ □□□□□□□ □□□ □□□□□□ □□□ □□□□ □□□ □□□□ □□□□□□ □□□□□□ □□□ □□□□□ □□□ .2
□□□□□□□□□□
3. PTFE Liner □□□□□□□ □□□□□□ □□□ □□□□□ □□□□□□ □□□□ □□□□
□□□□□ □□□□□□ □□□□□□□ □□□□□□□ □□□□□ □ □□□□□□□ □□□□ .4
□□□ □□□□□□□ □□□□□ □□□□□□□ □□□□□ □□ □□□□□□ □□□□ .5 lugged

DESIGN FEATURES

DURABLE :

· 1 piece non-welded PFA molded DSS Disc stem
· Precision casting WCB/CF8M Bodies

TRIPLE SEAL:

· Triple Seal:Spring loaded Mechanical seal,Radial Lip Seal,FPM
· China ONLY ONE Manufacturer 400Mpa Isostatic pressing PTFE seat,consistent density

ANTI-CORROSION:

· Material: Epoxy powder
· Coating Thickness:200-250μm
· Spraying temp: over 200℃. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

· 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
· ONLY ONE Manufacturer get CE certification up to DN1800
· 2 years warranty.15000 times On off test,30000 times Destructive experiment

Wafer

Lug

IMPERIAL DIMENSIONS:Inches										
Size	L	H1	H2	h	A	B	C	D	d	IS05211
NPS2	1.69	2.20	5.31	0.47	0.43	2.01	1.08	1.97	0.28	F05
NPS2 1/2	1.81	3.35	5.91	0.47	0.43	2.72	1.99	1.97	0.28	F05
NPS3	1.81	3.74	6.30	0.63	0.55	3.27	2.70	2.76	0.35	F07
NPS4	2.05	4.13	7.09	0.63	0.55	4.06	3.50	2.76	0.35	F07
NPS5	2.20	4.92	7.68	0.63	0.55	5.00	4.49	2.76	0.35	F07
NPS6	2.20	5.71	10.04	0.63	0.55	5.98	5.57	2.76	0.35	F07
NPS8	2.36	6.69	9.45	0.83	0.75	7.99	7.64	4.02	0.47	F10
NPS10	2.68	8.07	11.81	0.94	0.87	10.00	9.65	4.92	0.51	F12
NPS12	3.07	9.84	12.20	1.14	1.06	12.01	11.61	4.92	0.51	F12

APPLICATION SCENARIO

Industrial water application | Power plant | Sea water desalination | Water treatment | Water supply and drainage | HAVC | Food and drug | Water transport

RKSfluid
Proven Technology-Superior Features-Legendary Value

RKSfluid
Proven Technology-Superior Features-Legendary Value

RKSfluid
Proven Technology-Superior Features-Legendary Value

RKSfluid
Proven Technology-Superior Features-Legendary Value

RKSfluid
Proven Technology-Superior Features-Legendary Value

RKSfluid
Proven Technology-Superior Features-Legendary Value

COMPANY INFORMATION

i □□□□□□ □□□□□ □□□□□□□ □□□□□□□□□□□□□ □□□□□□□ □□ □□□□□□ □□□□□□ :□□□□□ □□□□.

ii □□□□□ □□□□□ CNC □□□□□ □ □□□□□ □□□□□□□ □□□□□□ □□□□□□ □ □□□□□□□ □□□□□□□□ □□□□□□ □ □□□□□□□□□ □□□□□□□ □□□□□□□□□ □□□□□□□.

iii □□□□□ □□□ □□□□□□□□ □□□□□ □□□□□□ □□□□□ □□ □□□□□□□□ □ □□□□□ □□ □□□□□□□□ □□□□□□□□ □□□□□□.

iv □□□□□□□ □□□□□□□□ □□ □ □□□□□ □ □□□□□□ □□ □□□□□□□□ □□□□□ □□□□□□ □□□□□□.

v □□□□□□ □□□□□: GB □ German Standard □ American Standard □ Tuv CE □ ISO 9001 □ ADWO-2000 □ TS □ PED □ WRC WRAS □ KTW □ API 6D □ API609.

□□□□□□□ □□□□□ □□□□□□ □ □□□ □□□□ □ □□□□□□□ □□□□ □ □□□□□ □□□□ □ □□□□□□□ □□□□ :□□□□□□□ □□□□□□□ □□□□□□ □□□□□□ □□□□□ □ □□□□□□□ / □□□□□ / □□□□ □□□□ □ □□□□□□□□ □□□□□□□ □.

01
21 years of professional experience
02
4 factories
03
Independent research and development team
28 top senior professional researchers
04
2 professional testing centers
05
100% high level ex-factory inspection
06
High quality imported materials
07
2 years quality assurance, repair and replacement

COMPANY QUALIFICATION

COMPANY EXHIBITION

Partners
TALIS
GEMÜ
WATTS
Bray
hawle
amri
BAYARD
AVK
EBRO
KEYSTONE
EMERSON
GIBSON
CAMERON
CMO VALVES
SWISS fluid
SAINT-GOBAIN
KSB
tyco
TTV
SAPAG
haike

Delivery
UPS
XDL
FedEx Express
EMS
TNT
DHL
Payment
PayPal
WESTERN UNION
VISA
ESCROW
MasterCard
HSBC

□□□□□□□□□□

□□□□□□□□ □□□□ □□□□□□□□□□ □□ □□□ □ □□□□□□ □□□ □□□□□ □□□ □□□ :□
A: .□□□□□□□□□□ □□□□ □ □□□□□□□□ □ □□□□□ □ □□□□□□□□ □□□□ □ □□□□□□□□□ □□□□

□□□□□ □□□□ □ □□□□□□□□□ □□□□□ □□□□□ □□ :□
A: □□□□□□□ □□□□□ □□□□□□ □ □□□□□□□□□□ □ □□□□□□□□.RKSfluid □□□□□□□□ □□□□□□□□□ □□□□□ □□□□□□□□
.□□□□□□ □□□ □ □□□□□□ □□□□.□□□□□□□□□□ □□□□□□□

□□□□□□□□□□ □□□□□ □□ □□ :□
□□□□□ :□ RKSfluid .□□□□□□□ □□□□ □□□□□□□□ □□□□ □□ □□□□ □□□□□ □□□□□ □□□

□□□□□□□ □□□□ :□
.□□□□□ □□□ □□□□□ □□□□□.□□□ □□□□ 5 ~ 2 □□ □□□□□ □□□ □□□□□□□ □□□□□□□□ :□

□□ :□
1 :□pc .□□□□□□□□ □□□□□

□□□□□□□ □□□□ □□ □□□□ :□
.□□□□□□ □□ □□□□□ □□□□□ □□ □□□□.□□□□□ □□□□ □□□□ □ □□□□□□□ □□□ □ 100 □□□□ □□□□□□ :□
□□□□□ □□□ □□□□□ TUV □ API □ WRAS □ CE □ ISO.
□□ □□□□□□□ □□□□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA.

□□□□□□□□□□ □□□□□□ □□□□□ □□□□ □□□□□ □□□□□ □□□ :□
A: RKSfluid ONWER 20 YERSTRESS □□□□□ 70 □□ □□□□□ □□□□□ R&D □□□□□□□ □□□□□ □□□□□ □□□□□□
□□ □□□□□□□ □□□□□□□□ □□□□□□□.