

00000 0000 00 000000000 00 00 000000 00000 000000000 000000 00000 00000000 00000000-00000
.000000 000000 000000 0 000000 0 00000000 000000 0000000000 00000 00 000000000.000000
.0000000000 00000 0000 000000 0000000000 00000000 000000000000

000000 00000: EN1092-2 / BS4504

00000 0000 00: DIN F4 / DIN F5 / BS 5163

DESIGN FEATURES



Features



- Use AkzoNobel material.
- Super Anti-corrosion
- Epoxy powder coating 200-250um,
- Baking varnish over 200°C,

| NO. | | |
|-----|----------------|------------------|
| 1 | Body | GGG50 |
| 2 | Dise | GGG40+EPDM |
| 3 | Wedge nut | C48600 |
| 4 | Stem | SS431 |
| 5 | Bonnet | GT450-10 |
| 6 | Gasket | EPDM |
| 7 | Y-ring | EPDM85-90 |
| 8 | Fix ring | CuZn21Si3/C69300 |
| 9 | Thrust bearing | C69300 |
| 10 | Seal ring | EPDM70 |
| 11 | O ring | NBR |
| 12 | Retainer ring | POM |
| 13 | Bushing ring | POM |
| 14 | Gland | SS431 |
| 15 | Dustproof ring | EPDM85 |
| 16 | Dise core | GGG40 |
| 17 | Bolt | SS316 |





Free wedge nut, reduces the stem bending forces and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to reduce the risk of bacterial growth.



One piece stainless steel stem in for better resistance to axial load and to with stand higher operating torques.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, prohibiting the introduction of foreign bodies at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



i 本公司 備有 各種 規格 之 鋼管 及 鋼板 等 材料 之 庫存 量 充足 。

ii 本公司 備有 CNC 加工 之 各種 規格 之 鋼管 及 鋼板 等 材料 之 庫存 量 充足 。

iii 本公司 備有 各種 規格 之 鋼管 及 鋼板 等 材料 之 庫存 量 充足 。

iv 本公司 備有 各種 規格 之 鋼管 及 鋼板 等 材料 之 庫存 量 充足 。

v 本公司 備有 各種 規格 之 鋼管 及 鋼板 等 材料 之 庫存 量 充足 。

本公司 備有 各種 規格 之 鋼管 及 鋼板 等 材料 之 庫存 量 充足 。

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



Faq

Q: How long does it take to receive the goods after payment?

A: .The delivery time depends on the quantity of goods and the destination.

Q: How do you ensure the quality of the goods?

A: .We have a strict quality control system. RKSfluid products are tested by independent third-party inspection companies.

Q: How long is the warranty period?

A: .RKSfluid provides a 2-year warranty for its products.

Q: How do you handle after-sales service?

A: .We have a professional after-sales service team. We can provide technical support and spare parts within 5-20 days.

Q: How do you ship the goods?

A: .We can ship by air, sea, or land.

Q: How do you ensure the safety of the goods?

A: .We use high-quality materials and advanced manufacturing technology. We have passed ISO 9001 certification.

Q: How do you ensure the safety of the goods?

A: .We have passed various international certifications, including TUV, API, WRAS, CE, ISO, DIN, ASME, BS, EN, JIS, API, and AWWA.

Q: How long has your company been in operation?

A: .RKSfluid has been in operation for over 20 years. We have a rich experience in R&D and production.

□□ □□□□□□ □□□□□□ □□□□□□.