

ٲٲٲٲ ٲٲٲٲٲ ٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲ ٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲ ٲٲٲٲٲ ٲٲ
 ٲٲٲ ٲٲٲٲٲ ٲٲ ٲٲٲٲ ٲٲٲ .ٲٲٲٲٲ ٲٲٲ ٲٲ ٲٲٲٲٲٲٲ ٲٲٲٲٲ ٲٲٲٲٲ ٲٲ ٲٲٲٲٲ ٲٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲٲ ٲٲٲٲٲٲ ٲٲٲٲ ٲٲ
 ٲٲٲٲ ٲٲٲ ٲٲ ٲٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲ ٲٲٲ.

COMPANY FACTORY



1. ٲٲٲٲ
- ٲٲٲٲٲٲٲ .2
3. NEEDٲE ٲٲٲٲ
- ٲٲٲٲٲٲ ٲٲ ٲٲٲٲ ٲٲٲ .4
- ٲٲٲٲٲ ٲٲٲٲ .5
- 6.strainer

:ٲٲٲٲٲٲٲٲٲٲٲ ٲٲٲٲٲٲٲٲ
 ٲٲٲٲٲ ٲٲٲٲ .1
 ٲٲٲٲٲ ٲٲٲٲٲ .2
 ٲٲٲٲٲٲ ٲٲٲٲ .3
 4

ٲٲٲٲٲ- ٲٲٲٲٲ ٲٲٲٲ (FB)					
DN	L	H2	H1	ٲ	ٲٲٲٲٲ
40	230	139	85	173	3/8 "



COMPANY INFORMATION



- i 100% 100% 100% 100% 100% 100% :100% 100%.
- ii 100% 100% CNC 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% .100% 100% 100% 100%.
- 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%.
- iv 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%.
- v 100% 100%: GB 100% German Standard 100% American Standard 100% Tuv CE 100% ISO 9001 100% ADWO-2000 100% TS 100% PED 100% WRC WRAS 100% KTW 100% API 6D 100% API609.
- 100% 100% 100% 100% 100% 100% 100% 100% 100% 100% :100% 100% 100% 100% 100% 100% 100% 100% / 100% / 100% 100% 100% 100% 100% 100%



COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□□□□□

□□□□□□□□ □□□□ □□□□□□□□ □□ □□ □ □□□□□□ □□□ □□□□□ □□□ □□□ :□
 □□□□□□□ □ □□□□□ □ □□□□□□□ □□□□ □ "□□□□□□" □□□□□□ :□.□□□□□□□□□ □□□□ □

□□□□□ □□□□ □ □□□□□□□□ □□□□□ □□□□ □□ :□
 □□□□□□ □□□□□ □□□□□ □ □□□□□□□□□ □ □□□□□□□ :□. RKSfluid □□□□□□□□ □□□□□□□□□ □□□□□□□□ □□□□□
 .□□□□□□□ □□□ □ □□□□□□ □□□□□ .□□□□□□□□□□ □□□□□□□□

□□□□□□□□□□ □□□□□" □□ □□ :□
 □: RKSfluid .□□□□□□□□ □□□□ □□□□□□□□□ □□□□ □□ □□□□ □□□□□ □□□□□ □□□□□ □□□□□

□□□□□□□ □□□□ :□
 .□□□□□□ □□□ □□□□□ □□□□□ .□□□□ □□□□□ 5 ~ 2 □□ □□□□□ □□□ □□□□□□□ □□□□□□□□ :□

□□ :□
 1 :□pc .□□□□□□□□□ □□□□□□

□□□□□□□ □□□□ □□ □□□□ :□
 .□□□□□□□ □□ □□□□□ □□□□□ □□ □□□□□ □□□□ □ □□□□□□□ □□□ □ 100 □□□□□ □□□□□□ :□
 □□□□□ □□□ □□□□□ TUV □ API □ WRAS □ CE □ ISO.
 □□ □□□□□□□ □□□□□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA.

□□□□□□ □□□□ □□□□ □□□ □□□□ □□□□ □□ :□

□: RKSfluid 000000 000000 000000 000000000 000000 00000000 70 00 000000 00000000 00 000000 27 000000 00 00000000 00000000 00000000 00000000.