





300	445	460	485	515	φ 400	φ 410	φ 430	φ 450	12- φ 23	12- φ 28	16- φ 31	16- φ 34	980	286	800	205
250	395	405	425	450	φ 350	φ 355	φ 370	φ 385	12- φ 23	12- φ 28	12- φ 31	12- φ 34	800	185	650	139
200	340	360	375		φ 295		φ 310	φ 320	8- φ 23	12- φ 23	12- φ 28	12- φ 31	650	129	520	76
150	285		300		φ 240			φ 250		φ 8-23		8- φ 28	520	70	370	39
100	220		235		φ 180			φ 190		φ 8-19		8- φ 23	370	34	300	28
80	200				φ 160				φ 8-19				300	26	220	15.5
50	165				φ 125				φ 4-19				220	14.5	-	-
DN	PN10	PN16	PN25	PN40	PN10	PN16	PN25	PN40	PN10	PN16	PN25	PN40	H(mm)	Weight (kg)	H(mm)	Weight (kg)
	φ D (mm)				φ K (mm)				N-φd (mm)				Full Bore		Reduced Bore	





# COMPANY FACTORY



I 本公司 備有 各種 規格 之 閘門 及 閘門 執行器 等 產品 均 係 採用 最 佳 材料 製造 而成 。

II 本公司 備有 CNC 加工 之 各種 規格 之 閘門 及 閘門 執行器 等 產品 均 係 採用 最 佳 材料 製造 而成 。

III 本公司 備有 各種 規格 之 閘門 及 閘門 執行器 等 產品 均 係 採用 最 佳 材料 製造 而成 。

IV 20000000 20000000 20000000 20000000 20000000 20000000 20000000 20000000.

V 20000000 20000000: GB 200000000 200000000 200000000 200000000 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609.

VI 200000000 200000000 20000000 200000000 200000000 200000000 200000000 200000000 :200000000 200000000 20000000 20000000000 / 200000000 / 200000000 200000000 2000000000 2000000000.





## COMPANY QUALIFICATION



## COMPANY EXHIBITION



## Partners



### Delivery



### Payment



:□□□□□□□□

□□□□□□□□ □□□□ □□□□□□□□ □□ □□ □□□□□□ □□ □□ □□□□ □□ □□ □□ :□

.□□□□□□ □□□□ □□□□□□ □□□□□□ □□□□ □□□□□□□□ □□□□ :□

□□□□□ □□ □□□□□□□□ □□□□□ □□□□ □□ :□

□□□□□□ □□□□□□ □□□□□□□□□□ □□□□□□□□ □□□□□□ □□□□□□ :□. RKSfluid □□□□□□□□ □□□□□ □□□□□□□□

.□□□□□□ □□□ □□□□□□ □□□□□□□□ □□□□□□□□ □□□□□□□□

□□□□□□□□□□ □□□□□ □□ □□ □□ :□

