

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



A diagram of a horizontal beam of length L . A triangular load is applied to the left half of the beam, starting from 0 at the left end and increasing linearly to a peak value of w_0 at the midpoint. The right half of the beam is free of load. A reaction force R is shown at the right end of the beam, pointing upwards.



I _____

[illegible]

III. 000000 000 000000000 000000 000000 000000 00 000000000 000000000 000000000 000000000 0000000.

IV _____

V 认证标准: GB 认证标准 认证标准 认证标准 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609.

VI. အခြားအရေးကြီးသော အချက်အလက်များ : အခြားအရေးကြီးသော အချက်အလက်များ မရှိပါ။



COMPANY EXHIBITION



COMPANY QUALIFICATION



Partners



Delivery



Payment



:□□□□□□□□

□□□□□□□□ □□□□ □□□□□□□□ □□ □□ □□□□□□ □□ □□ □□□□ □□ □□ :□
.□□□□□□ □□□□ □□□□□□ □□□□□□ □□□□ □□□□□□□□ □□□□ :□

□□□□□ □□ □□□□□□□□ □□□□ □□□□ □□ :□
□□□□□ □□□□□ □□□□□□□□□□ □□□□□□□□ □□□□□□ □□□□□□ :□. RKSfluid □□□□□□□□ □□□□ □□□□□□□□
.□□□□□□ □□ □□□□□□ □□ □□□□□□□□ □□□□□□□□

□□□□□□□□□ □□□□ □□ □□ :□
□: RKSfluid .□□□□□□ □□□□ □□□□□□□□ □□□□ □□□□□ □□□□ □□□□ □□□□

□□□□□□ □□□□ :□
.□□□□□ □□ □□□□ □□□□□ □□□ □□□□ 5 ~ 2 □□ □□□□ □□□□ □□□□□□ □□□□□□□□ :□

□□□□ :□
.□□□□□□□ □□□□ □□□□ 1 :□

□□□□□□ □□□□ □□ □□□□ :□
.□□ □□□□□ □□□□□ □□ □□□□□ □□□□ □□□□ □□□□□□□□ □□□□ %100 □□□□□ □□□□□□ □□□□□□ :□
□□□□□ □□ □□□□□ □□□□ TUV□ API□ WRAS□ CE□ ISO.
□□ □□□□□□ □□□□□□□□ DIN□ ASME□ BS EN□ JIS□ API□ AWWA.

□□□□□□□□ □□□□□ □□□□□ □□□□ □□□□ □□□□ □□□□ :□
□: RKSfluid □□□□□ □□□□□ □□ □□□□□ □□□□□□□□ □□□□□ □□□□□□□□ 70 □□ □□□□□ □□□□□□ □□ □□□□□ 27 □□□□□□
□□□□□□□ □□□□□□□ □□□□□□□□.