



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings



Resilient seat butterfly valve



Resilient seat butterfly valve



Resilient seat butterfly valve

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: DI+ Nylon

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange



Resilient seat butterfly valve



Double flange resilient seat butterfly valve



Short-neck butterfly valve for petroleum

PN10/PN16, ANSI 125LB/150LB,5K/10K

Size:DN25-DN2400

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Wafer, Lug, Flange

PN10/PN16, ANSI 125LB/150LB, 5K/10K

Size:DN50-DN1000

Body:DI CI

Disc: Stainless steel

Seat :EPDM, NBR, Viton

Connection: Flange

ANSI 125LB/150LB

Top Flange Standard:ISO5211

Size:2"-12"

Body: DI CI

Disc :Stainless Steel

Seat : EPDM, NBR, Viton

Connection:Wafer, Lug



PTFE Butterfly Valve



PTFE Butterfly Valve



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: Ductile Iron+PTFE

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug



PTFE Butterfly Valve



PTFE Butterfly Valve



PTFE Butterfly Valve

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB, CF8, CF8M

Disc: CF8+PTFE, CF8M+PTFE

Seat: PTFE

Connection: Wafer, Lug

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: Ductile Iron

Disc: CF8, CF8M

Seat: PTFE

Connection: Wafer, Lug, Flange

BSEN 1092, DIN 2501, ANSI, JIS, AS2129

Size: DN50~DN600

Body: WCB

Disc: CF8 +PTFE, CF8 +PFA

Seat: PTFE

Connection: Wafer, Lug, Flange

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



للسوائل في عام 1997. نحن ورشة إنتاج للمسبك والقطع ومركز الأبحاث RKS تأسست شركة وخلايا معالجة احترافية CNC والتطوير ومركز فحص الجودة. تشمل مرافق التصنيع مراكز تصنيع ومعدات لحام واسعة النطاق وخطوط تجميع وطلاء أوتوماتيكية. لقد قمنا ببناء فريق للتصميم والبحث والتطوير. أصبح مركز الاختبار الجديد الخاص بنا كمركز اختبار لمنصة الخدمة العامة في القياسي للوحدة المرجعية للصمامات الصينية ، للمشاركة في تطوير GB أصبح ، Liaoning مقاطعة معايير صناعة الصمامات ذات الصلة. من أجل تسريع التوسع في الأعمال التجارية الخارجية وتكامل في الولايات المتحدة الأمريكية والألمانية وروسيا. لدينا RKS الموارد ، ودعم نجاح مبيعات السوائل المعيار الألماني والأمريكي ، المعتمدة من ، ISO ، GB ، وكييل أمريكي. معايير تصميم منتجاتنا تغطي منتجاتنا: الصمامات الكروية اليدوية ، API ، TS ، ISO9001 ، ADWO-2000 و CE و TUV قبل والهوائية والكهربائية وصمامات الفراشة وصمامات البوابة. فحص الصمامات ، صمامات التحكم الآلي. المسبوكات والتجهيزات: أجسام الصمامات ، والأقواس ، والأقراص ، والسيقان ، وعلبة التروس ، والوصلات العالمية ، ومحولات الشفة ، والتنصت على السروج. "كفلسفة قيمة منتجاتنا. ارضا العملاء هو هدفنا في العمل!

Our Factory



Exhibition Photos



Our Certificates

