



DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment





APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



Company Advantages



i

ii

iii

iv

v GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRA KTW API 6D API609

VI

Exhibition Photos



Our Certificates



□□□□

□□□□□□□□□□□□□□□□□□

- 00000000000000000000000000

0000000000000000

- 0000000000Hrdraulic000000 RKSfluid000000000000000000000000

00000000000000

00RKSfluid000000000000000000

0000000000

00000000020500000000000000000000

00Moq.

A00000001PC

0000000000

- 00000010000000000020000000000000

000000TUV00API00WRA00CE00ISO0000

000000DIN00ASME00BS EN00JIS00API00AWWA

0000000000000000

00RKSfluid002000000070000000000000000000000000

2 4 6 800000000IV