

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300, PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600, PN10/16/25



**LARGE DIAMETER
METAL SEATED GATE VALVE**
DN700-DN2000, PN10/16/25

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY INFORMATION



i. 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

ii. CNC 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

iii. 100% 100% 100% 100% 100% 100% 100% 100% 100% 100%

iv

v GB TUV CE ISO 9001 ADWO-200 TS PED WRC WRAS KTW KTW API 6D API609

/ /



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□

□□□□□□□□□□□□
TO□□□□□□□HRDRAULIC□□□□□ RKSfluid □□□□□□□□□□□□□□□□

100% 100%
 RKSfluid 100%

D
 25

D
 1

100% 100%
 100% 100%
 TUV API WRAS CE ISO
 DIN ASME BS EN JIS API AWWA

100% 100%
 RKSfluid 20 70