



RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve




Pipe Fittings

DESIGN FEATURES

VERSATILE & RANGE

- Up to **27mm** of tolerance, **DN40 ~ DN300** stock reduction
- Allows angular deflection of **+/-5°**
- Covering most common pipe materials



USER FRIENDLY

- **Economical** and **applicable**
- **Easy Operation**


OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- **Anti-corrosion**
- Thickness: Epoxy powder coating of **200-250µm**
- Temperature : Spraying temperature over **200 °C**. Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: **EN-GJS-500-7** , nodularity over **95%**!



APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages



I 100% high level ex-factory inspection

II CNC processing

III 21 years of professional experience

IV 2 years quality assurance, repair and replacement

V GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API609

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□RKSfluid□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□2~5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□MOQ

□□□□□□□□1pc□

□□□□□□□□□□□□□□□□□□□□

□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□TUV□API□WRAS□CE□ISO□□□□

□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□70□□□