



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  , Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment







## APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06





I 工厂

II 工厂CNC

III 工厂

IV 工厂

V 工厂GB 工厂TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

工厂 工厂

## Exhibition Photos



# Our Certificates



□□□□

□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□

□□□□□□□□□□□□  
 □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□  
 □□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□□□  
 □□□□□□□2~5□□□□□□□□□□□□□□□□□□□□

□□ MOQ  
 □□□□□□□□1pc□

□□□□□□□□□□  
 □□□□□100□□□□□□2□□□□□□□□□□□□□□□□□  
 □□□□□TUV□API□WRAS□CE□ISO□□□□  
 □□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□

RSfluid 2070