



FB

| Dn | l | H2 | w | |
|-----|-----|-----|-----|------|
| 40 | 230 | 139 | 173 | 3/8" |
| 50 | 230 | 139 | 173 | 3/8" |
| 65 | 290 | 159 | 198 | 3/8" |
| 80 | 310 | 179 | 226 | 3/8" |
| 100 | 350 | 214 | 265 | 1/2" |
| 125 | 400 | 278 | 307 | 1/2" |
| 150 | 480 | 333 | 351 | 1/2" |
| 200 | 600 | 600 | 436 | 3/4" |
| 250 | 700 | 730 | 524 | 1" |
| 300 | 850 | 850 | 606 | 1" |

Highlights

1. DN+2
- 2.
- 3.
4. 100 64
5. FB RB ACD
- 6.
- 6.1 $1.1 * PN + 1 \text{ bar}$
- 6.2 $1.5 * PN + 1 \text{ bar}$
- 6.3 0.2 bar
7. 1000 Hz
- 8.
- 9.

✓ GB ✓ TUV CE ✓ ISO 9001 ✓ ADWO-2000 ✓ TS ✓ PED ✓ WRC WRAS ✓ KTW ✓ KTW ✓ API 6D ✓ API609 ✓
✓ VI ✓ / ✓ / ✓

COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□hrdraulic□□□□□□RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□

□□RKSfluid□□□□□□□□□□□□

□□□□□□□□

□□□□□□□2□5□□□□□□□□□□□□□□□□□□

□□□□

□□□□□□□1□□

□□□□□□□□□□

□□□□□100□□□□□□□2□□□□□□□□□□□□□□

□□□□□TUV□API□WRAS□CE□ISO□□□□

□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□□□□70□□□□□□□□□□□□□□□□□□□□□□