

**SLAM**

- - 
  -
- EN 558-1 ISO 5752 EN 1092-2 ISO 7005-2



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design. Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

DN	DN50 -DN600 NPS2 -NPS24
PN	PN10/16/25
Temp	0°C +80°C
Material	
Coating	
Standard	GB/T 12235-2007
EN Standard	EN 558-1
EN Standard	EN 1092-2



NPS2-NPS14 (DN50-DN350)



NPS16-NPS24 (DN400-DN600)



# COMPANY INFORMATION



i. 公司基本情况

ii. CNC 加工中心

iii. 质量管理体系

iv. 生产流程

v. 公司符合 GB、TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、KTW、API 6D、API609

vi. 公司主要客户 / 合作伙伴

# COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

# COMPANY QUALIFICATION



# COMPANY EXHIBITION



## Partners



□□□□

□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□  
 □□□□□□□hrdraulic□□□□□RKSfluid□□□□□□□□□□□□□□□□

□□□□□□□□□□  
 □□RKSfluid□□□□□□□□□□□□□□

Ø150  
Ø150×25

Ø100  
Ø100×10

Ø150  
Ø150×100×2  
TUV API WRAS CE ISO  
DIN ASME BS EN JIS API AWWA

RKSfluid  
Ø150×70