



4. 规格

规格 - 规格 (FB)					
DN	L	2	H1		
40	230	139	85	173	3/8"
50	230	139	85	173	3/8"
65	290	159	95	198	3/8"
80	310	179	102	226	3/8"
100	350	214	112	265	1/2"
125	400	278	127	307	1/2"
150	480	333	145	351	1/2"
200	600	600	172	436	3/4"
250	730	730	205	524	1"
300	850	850	232	606	1"

规格

1. 规格 DN2 mm

2. 规格

3. 规格

4. 规格 64 规格

5. 规格 FB 规格 RB 规格 ACD

6. 规格

6.1 规格 1.1 \* PN 1 Bar

6.2 规格 1.5\*PN1Bar

6.3 规格 0.2 Bar



I

II

III

IV

V TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

VI



### COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□

□: □□□□□□□□□□□□□□□□  
 □□□□”□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□  
 A□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□  
 A□ □□□□□ 2~5 □□□□□□□□□□□□□□□□□□□□

□: □□□□□□  
 □: □□□□ 1 □□

□: □□□□□□□□□□  
 □: □□□□ 100% □□□□□□2 □□□□□□□□□□□□□□□□□□□

TUV API WRAS CE ISO  
DIN ASME BS EN JIS API AWWA

:  
A RKSfluid 27 70