

https://www.alibaba.com/product-detail/DIN-STANDARD-CAST-IRON-METAL-SEAL_1600089458994.html?spm=a2747.manage.0.0.516371d2z5mxtO



RKSfluid®
A key Valve in Flow Control

Butterfly Valve Ball Valve Gate Valve Globe Valve Check Valve Pipe Fittings

The image is a promotional graphic for RKSfluid. It features a central logo with a stylized eagle and the text 'RKSfluid®' and 'A key Valve in Flow Control'. Below the logo, six different types of valves and pipe fittings are displayed on a dark background with blue lighting effects. Each item is labeled with its name in a small box at the bottom: Butterfly Valve, Ball Valve, Gate Valve, Globe Valve, Check Valve, and Pipe Fittings. The background also shows a complex industrial piping system.

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category





XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX/XX/XXXXXXXXXXXXXXXX

Our Factory



Exhibition Photos



Our Certificates



□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□

□□□□□□□□□□

