




Pressure ratings:PN10 PN16

Body:Ductile Iron

Trim:SS304 SS316 etc

Connection: ARVS/KARS-BPT threaded, KARX-Flanged

Working temperature: $-10^{\circ}\text{C}\sim+80^{\circ}\text{C}$



1. 2. 3. 4. 5. comply BS EN 1074-4

COMPANY INFORMATION



RKSfluid 1997 Foundry CNC GB RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API
RKS GB ISO TUV CE ADWO-2000 ISO9001 TS API

i CNC

ii CNC

iii

iv

v GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW KTW API 6D API609

VI

01

21 years of professional
experience

03

Independent research and
development team
28 top senior professional
researchers

05

100% high level ex-factory
inspection

07

2 years quality assurance,
repair and replacement

4 factories

02

2 professional testing
centers

04

High quality imported
materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□

hrdraulicRKSfluid

RKSfluid

25

1

1002

TUVAPIWRASCEISO

DINASMEBS ENJISAPIAWWA

RKSfluid2070