

DESIGN FEATURES





● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS









SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



**LARGE DIAMETER
METAL SEATED GATE VALVE**
DN700-DN2000,PN10/16/25



1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18

II □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

III □□□□□□□□□□□□□□□□□□□□□□

□ □

Tuv CE ISO 9001 ADWO-200 TS PED WRC WRAS KTW API 6D API609

[illegible]



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□: □□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□
□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□

□: □□□□□□□□□□

□□ RKSfluid □□□□□□□□□□□□□□□□

D□□□□□□

□□ □□□□2 ~ 5□□□□□□□□□□□□□□□□□□□□

D□□□□□□

□: □□□□ 1 □□

□: □□□□□□□□

□: □□□ 100% □□□□□2 □□□□□□□□□□□□□□□□

□□□□Tuv□Api□Wras□CE□ISO□□□□

□□□□ DIN□ASME□BS EN□JIS□API□Awwa□

□: □□□□□□□□□□□□□□□□

□□ RKSfluid □□27□□□□□70□□□□□□□□□□□□□□□□□□□□