

RKSfluid®



规格	DN32 - DN2400 (NPS1 1/4-NPS96)
压力等级	PN6 - PN10 - PN16 (150 psi)
温度范围	-40°C-120°C
密封材料	氟橡胶
衬里材料	NBR/EPDM
连接方式	法兰/承插/焊接

APPLICATION SCENARIO

Industrial water application	Power plant	Sea water desalination	Water treatment	Water supply and drainage	HAVC	Food and drug	Water transport





01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Delivery



Payment



□□□□

□: □□□□□□□□□□□□□□□□
□□□□"□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□
A□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□
A□ □□□□ 2~5 □□□□□□□□□□□□□□□□

□: □□□□□
□: □□□□ 1 □□

□: □□□□□□□□
□: □□□ 100% □□□□□2 □□□□□□□□□□□□□□□□
□□□□□ TUV□API□WRAS□CE□ISO □□□□
□□□□□ DIN□ASME□BS EN□JIS□API□AWWA□

□: □□□□□□□□□□□□□□□□
A□ RKSfluid □□20□□□□70□□□□□□□□□□□□□□□□□□□□□□□□□□□□