



GL - series GL系列

Bidirectional lug-wafer design knife gate valve. "Monoblock" one-piece cast iron body. Stainless steel gate. Two rubber sleeves. Provides high flow rates with low pressure drop.

APPLICATIONS:

Suitable for working in the mining industry, in loaded fluid transport lines, such as: water with rocks, sludge, etc. and generally used for abrasive fluids in chemical industry and waster water. Mining, Sewage treatment - Oil industry, Electrical power stations, Chemical plants, Energy Sector, Thermal power stations.

SIZES:

DN50 to DN1400 (larger sizes on request).

WORKING (ΔP):

DN50 $\rightarrow$ DN600:	10 kg/cm ²
DN700 $\rightarrow$ DN1400:	6 kg/cm ²

FLANGE DRILL:

DIN PN10 & ANSI B16.5 (150 LB).

双向突耳对夹式刀闸阀：“整体”一体式铸铁机身，不锈钢闸门，有两个胶套。流速高和阻力低。

应用:

适用于采矿业、装载流体输送管线，如：含岩石和污泥的水，一般用于化工和废水中的磨料液。可用于采矿、污水处理--石油工业、发电站、化工厂、能源部门、火电站。

尺寸:

DN50 to DN1400 (可根据要求提供更大尺寸)。

Δ 工作压力:

DN50 $\rightarrow$ DN600:	10 kg/cm ²
DN700 $\rightarrow$ DN1400:	6 kg/cm ²

法兰钻孔:

DIN PN10 & ANSI B16.5 (150磅)。