





FB

Dn	l	H2	w	
40	230	139	173	3/8"
50	230	139	173	3/8"
65	290	159	198	3/8"
80	310	179	226	3/8"
100	350	214	265	1/2"
125	400	278	307	1/2"
150	480	333	351	1/2"
200	600	600	436	3/4"
250	700	730	524	1"
300	850	850	606	1"

### Highlights

1. DN+2
- 2.
- 3.
4. 100 64
5. FB RB ACD
- 6.
- 6.1  $1.1 * PN + 1 \text{ bar}$
- 6.2  $1.5 * PN + 1 \text{ bar}$
- 6.3 0.2 bar
7. 1000 Hz
- 8.
- 9.



✓ GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW KTW API 6D API609  
✓ 100% 100% 100% 100% 100% 100% / 100% / 100%

## COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

## COMPANY QUALIFICATION



## COMPANY EXHIBITION





□□□□□□□□□□

□□RKSfluid□□□□□□□□□□□□

□□□□□□□□

□□□□□□□2□5□□□□□□□□□□□□□□□□□□

□□□□

□□□□□□□1□□

□□□□□□□□□□

□□□□□100□□□□□□□2□□□□□□□□□□□□□□

□□□□□TUV□API□WRAS□CE□ISO□□□□

□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□□□□70□□□□□□□□□□□□□□□□□□□□□□