



## DESIGN FEATURES

### VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of  $\pm 3^\circ$  per gasket
- Covering most common pipe materials



### OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

### DURABLE

- **ANTI-CORROSION**
- Thickness: **Epoxy powder** coating of **200-250 $\mu$ m**
- Temperature : Spraying temperature over **200 $^\circ$ C**
- Doesn't fade, even wipe with **diethyl ether**

### MATERIAL

- Epoxy powder: **AkzoNobel**, Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled

### APPLICATION SCENARIO



## Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂内部环境

II CNC 加工车间

III 仓库

IV 办公室

V 工厂通过 GB 认证、TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、API 6D、API609

工厂地址：中国浙江省宁波市北仑区新碶街道新碶社区新碶村新碶路 1 号

## Exhibition Photos



# Our Certificates



□□□□

□□□□□□□□□□□□□□□□  
□□□□□□□□□□□□□□□□

□□□□□□□□□□□□  
□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□

□□□□□□□□□□  
□□RKSfluid□□□□□□□□□□□□□□□□

□□□□□□□□  
□□□□□□□2~5□□□□□□□□□□□□□□□□□□□□

□□MOQ  
□□□□□□□□1pc□

□□□□□□□□□□  
□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□  
□□□□□TUV□API□WRAS□CE□ISO□□□□  
□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□

RKSfluid2070