

DESIGN FEATURES

DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

ANTI-CORROSION

- Material: Epoxy powder:  Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



I 公司总部

II 分公司

III 办事处

iv 代理商

v 认证 GB 认证 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRA KTW API 6D API609

VI 产品 [蓝色](#) 认证/标准/规格



COMPANY QUALIFICATION



COMPANY EXHIBITION



□□□□

□□□□□□□□□□□□□□□□

- □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□

- □□□□□□□□Hrdraulic□□□□ RKSfluid□□□□□□□□□□□□□□□□□□

□□□□□□□□□□

□□RKSfluid□□□□□□□□□□□□□□

□□□□□□□□

□□□□□□□□2□5□□□□□□□□□□□□□□□□□□□

□□**Moq.**

A□□□□□□□□1PC□

□□□□□□□□□□

- □□□□□□100□□□□□□□□□□2□□□□□□□□□□□□□□

□□□□□□TUV□API□WRA□CE□ISO□□□□

□□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□□70□□□□□□□□□□□□□□□□□□□□□□

