



6.PN10/16/25



DN	L	H	H1	DN	L	H	H1
40	230	139	85	250	□730□	□476□	205
50	230	139	85	300	850	□526□	□232□
65	290	159	95	350	980	□585□	□262□
80	310	179	102	400	1100	624	□292□
100	350	214	112	500	1250	720	360
125	400	278	127	600	1450	□835□	□424□
150	□480□	233	145	800	1850□	1110	515
200	600	407	172	1000	2250	1350	630

□□□

1. □□□□□□□□ DN2 mm
2. □□□□□□□□□□□□
3. □□□□□□□□□□□□
4. □□□□□□□□□□64□□□□□

5. (FB) (RB) (ACD) 6

6.1 1.1 \* PN 1 Bar

6.2 1.5 \* PN 1 Bar

6.3 0.2 Bar

7. 1000 Hz

8. 9.



# COMPANY INFORMATION



I 公司位于中国江苏省无锡市

II 公司占地面积约 100000 平方米

III 公司拥有先进的生产设备和

完善的质量管理体系

V 公司通过了 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、API 6D、API609

等认证，产品广泛应用于石油、化工、冶金等行业

# COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

# COMPANY QUALIFICATION



## COMPANY EXHIBITION



## Partners





