



RKSfluid®
Reliability Keeps Safety



```
1□□□□□□□□□□□□□□□□
2□□□□□□□□□□□□□□
3□□□□□□□□□□□□□□
4□□□□□□□□□□□□DOE□22226□
```




产品特点

1. 采用优质不锈钢材料
2. 工作压力可达1MPa
3. 结构紧凑，占地面积小
4. 操作简便，维护方便

COMPANY INFORMATION





1. 100% PP
2. 100%
3. Supply API, AWWA, ASME, BS, EN, DIN, JIS Standard, TUV, CE, ISO9001, TS, OHSAS, WRAS
4. 100%

Exhibition Photos



Our Certificates



□□□□

Q1□□□□□□□□□□

A1□□□□□□□□□□□□□□

Q2□□□□□□□□□□

A2□□□□□□□5-10□□□□□□□□□□□□□□□□15-90□□

□□**3**□□□□□□□□

A3□T/T 30□□□□□□□□□□□□□□□□□□□□□□□□

Q4□□□□□□□□□□□□□□□□□□

A4□□□□□□□□1PC□□□□□□□□□□□□□□□□□□□□□□

Q5□□□□□□□□□□□□□□□□□□□□□□

A5□□□□□100□□□□□□□□□□□□□□□□□□□□

□□**6**□□□□□□□□□□□□□□□□□□□□□□

A6□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□**7**□□□□□□□□□□□□□□□□□□□□□□

A7□□□1□□□□□□□□□□□□□□□□□□□□□□□□□□□□