




DESIGN FEATURES

RANGE

- For DI, AC, PVC and Fibre cement pipes
- Dimension from 32-315mm



LOW COST

- Structure compact and convenient operation

RELIABLE

- EPDM gasket to EN681-1
- Anti-corrosive coating
- Bichromated bolts on series 790

MATERIAL

- S700 & S750: Grey Cast Iron EN-GJL-250 Quality
- S790: ductile iron EN-GJS-400-15 Quality

APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



Our Factory



Company Advantages



I 工厂占地面积 100000 平方米

II 拥有 CNC 加工中心 100 余台

III 拥有 2 个专业的检测中心

IV 拥有 2 年的质量保证、维修和更换

V 通过了 GB 认证，并通过了 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC、WRAS、KTW、API 6D、API609 认证

□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□

□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□

□□RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□

□□□□□□□□2~5□□□□□□□□□□□□□□□□□□□□□□□□

□□MOQ

□□□□□□□□1pc□

□□□□□□□□□□□□

□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□TUV□API□WRAS□CE□ISO□□□□□

□□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□□70□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□