



- **Suitable** for viscous liquid, V-shaped gap, flow stability, not easy to block
- **High-strength** structure, mesh screen without deformation, high safety factor, flexible increase in the number of units
- The outer surface of the filter element is smooth and easy to clean. Automated operation, backwashing consumes less liquid
- Tolerate high-intensity positive and negative pressure
- Precision filtration, accuracy range **25-500** μm
- 304, 316L material, corrosion resistant

Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



1. 100% PP
2. API AWWA ASME BS EN DIN JIS TUV CE ISO9001 TS OHSAS WRAS R& D
3. API AWWA ASME BS EN DIN JIS TUV CE ISO9001 TS OHSAS WRAS R& D

Exhibition Photos



Our Certificates





□□□□

Q1□□□□□□□□□□

A1□□□□□□□□□□□□□□

Q2□□□□□□□□

A2□□□□□5-10□□□□□□□□□□□15-90□□

□□3□□□□□□□□

A3□T / T 30□□□□□□□□□□□□□□□□□□□□□□

Q4□□□□□□□□□□□□□□□□□□

A4□□□□□□□1pc□□□□□□□□□□□□□□□□□□□

Q5□□□□□□□□□□□□□□□□□□

A5□□□□100□□□□□□□□□□□□□□

Q6□□□□□□□□□□□□□□□□

A6□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□7□□□□□□□□□□□□

A7□□□1□□□□□□□□□□□□□□□□□□