



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



**LARGE DIAMETER
METAL SEATED GATE VALVE**
DN700-DN2000,PN10/16/25



Water transport



The diagram shows a horizontal beam of total length $2L$. A central support is located at the midpoint. A downward force F is applied at the midpoint. The beam is divided into two segments of length L on either side of the support. The left end of the beam is labeled $x=0$ and the right end is labeled $x=2L$. The beam is shown in a slightly deformed state, with a downward deflection at the center.

[illegible]

V GB TUV CE ISO 9001 ADWO-200 TS PED WRC WRAS KTW API
6D API609
/ /



RKSfluid[®]
www.rksfluid.com

RKSfluid (Yingkou) Flow Control Company



SGS CE WRAS

□□□□□□

□: □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□

□□□□□□□□□□□□ RKS□ □□□□□□□□□□□□□□□□

□: □□□□□□□□□□

□□RKSfluid □□□□□□□□□□□□□□

D□□□□□□

A: □□□□2 ~ 5□□□□□□□□□□□□□□□□□□

D: □□□

□: □□□□ 1 □□

□: □□□□□□□

□: □□□ 100% □□□□□2 □□□□□□□□□□□□□□

□□□□□Tuv□Api□Wras□CE□ISO□□□□

□□□□ DIN□ASME□BS EN□IS□API□Awwa□

□: □□□□□□□□□□□□□□□□

□□RKSfluid□□27□□□□□70□□□□□□□□□□□□□□□□□□□