



# RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve




Pipe Fittings

## DESIGN FEATURES

### VERSATILE & RANGE

- Up to **27mm** of tolerance, **DN40 ~ DN300** stock reduction
- Allows angular deflection of **+/-5°**
- Covering most common pipe materials



### USER FRIENDLY

- **Economical** and **applicable**
- **Easy Operation**


### OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

### DURABLE

- **Anti-corrosion**
- Thickness: Epoxy powder coating of **200-250µm**
- Temperature : Spraying temperature over **200 °C**. Doesn't fade, even wipe with **diethyl ether**

### MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!





## APPLICATION SCENARIO



Industrial water application



Hydroelectric generation



Sewage treatment



Water treatment



Water supply and drainage



Water transport



Pipe network in house



Irrigation



## Our Factory





# Company Advantages



I 100% high level ex-factory inspection

II CNC precision processing

III professional testing centers

IV 2 years quality assurance, repair and replacement

V GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API609





