

产品特点

- 结构紧凑
- 使用寿命长
- 维护方便

技术参数

- 口径: DN50 - DN600
- 压力: PN10/16/25
- 温度: 0°C~80°C
- 材质: 碳钢/不锈钢
- 密封: EPDM/NBR
- 标准: EN 558-1, ISO 5752, EN 1092-2, ISO 7005-2



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design. Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

口径	DN50 - DN600 (NPS2-NPS24)
压力	PN10/16/25
温度	0°C~80°C
材质	碳钢/不锈钢
密封	EPDM/NBR
标准	GB/T 12235-2007
执行	EN 558-1
符合	EN 1092-2



NPS2-NPS14 (DN50-DN350)



NPS16-NPS24 (DN400-DN600)



COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□: □□□□□□□□□□□□□□
□□□□”□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□
□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□

□: □□□□□□□□□□
A□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□
A□ □□□□ 2~5 □□□□□□□□□□□□□□□□

□: □□□□□
□: □□□□ 1 □□

□: □□□□□□□□
□: □□□ 100% □□□□□2 □□□□□□□□□□□□□□
□□□□□ TUV□API□WRAS□CE□ISO □□□□
□□□□□ DIN□ASME□BS EN□JIS□API□AWWA□

□: □□□□□□□□□□□□□□□□□□
A□ RKSfluid □□20□□□□70□□□□□□□□□□□□□□□□□□□□