

DESIGN FEATURES

This series of butterfly valves are used for industrial pipelines, as bi-directional open and close and regulation devices, the adjustment range is from 40°C-90°C full open. Suitable temperature $\geq 80^{\circ}\text{C}$

Features

- Size range DN100-1200mm
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel /WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-SS420/SS431/SS316
- Fusion bonded epoxy coating-Min 300 Microns



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



I 公司位于中国山东省潍坊市青州市

II 公司占地面积约 1000 亩

III 公司注册资金 10000 万人民币

IV 公司主要产品为

V 公司通过了 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRAS、KTW、API 6D、API609

等认证，产品广泛应用于石油、化工、冶金等行业。

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



□□□□□

□: □□□□□□□□□□□□□□
 □□□□"□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□
 □□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□
 A □ RKSfluid □□□□□□□□□□□□□□□□□□

□□□□□□
 A □ □□□□□ 2~5 □□□□□□□□□□□□□□□□□□

□: □□□□□
 □: □□□□□ 1 □□

□: □□□□□□□□□□
 □: □□□ 100% □□□□□□2 □□□□□□□□□□□□□□
 □□□□□ TUV□API□WRAS□CE□ISO □□□□
 □□□□□ DIN□ASME□BS EN□JIS□API□AWWA□

□: □□□□□□□□□□□□□□□□
 A □ RKSfluid □□27□□□□□70□□□□□□□□□□□□□□□□□□□□□□□□