




RKSfluid®

A key Valve in Flow Control



Butterfly Valve



Ball Valve



Gate Valve



Globe Valve



Check Valve



Pipe Fittings

Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category





I 工厂

II CNC 加工

III 铸造

iv 锻造


v 符合 GB、TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC WRA、KTW、API 6D、API609

VI 符合 ISO 9001、ISO 14001、OHSAS 18001、API 6D、API 609

Four factories



Why choose us



- Hrdraulic RKSfluid

RKSfluid

25

Moq. A 1PC

100 2 TUV API WRA CE ISO DIN ASME BS EN JIS API AWWA

RKSfluid 20 70