

## DESIGN FEATURES



### ● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

### ● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



**RELATED PRODUCTS**



**SMALL DIAMETER GATE VALVE**  
DN50-DN300,PN10/16/25



**METAL SEATED GATE VALVE**  
DN350-DN600,PN10/16/25



**LARGE DIAMETER METAL SEATED GATE VALVE**  
DN700-DN2000,PN10/16/25

# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



## COMPANY INFORMATION



RKS Fluid 1997 100% CNC GB ISO TUV for CE ADWO-2000 TS API “

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

# COMPANY QUALIFICATION



# COMPANY EXHIBITION



□□□□

□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□  
 □□□□□□□ hydraulic □□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□  
 □□ RKSfluid □□□□□□□□□□□□□□

□□□□□□□□  
 □□□□□□□ 2 □ 5 □□□□□□□□□□□□□□□□□□□□□□□□

□□□  
 □□□□□□□ 1 □□

□□□□□□□□□□□□  
 □□□□□ 100 □□□□□□□ 2 □□□□□□□□□□□□□□□□□  
 □□□□□ TUV □ API □ WRAS □ CE □ ISO □□□□  
 □□□□□ DIN □ ASME □ BS EN □ IS □ API □ AWWA □

□□□□□□□□□□□□□□□□□□  
 □□ RKSfluid □□ 20 □□□□□□□□ 70 □□□□□□□□□□□□□□□□□□□□□□