

DESIGN FEATURES



● TECHNICAL REQUIREMENT

- 1.Design standard:BS 5163.
- 2.Face to face:BS 5163.
- 3.Flanges standard:BS EN1092-2:1997 PN16.
- 4.Test standard:BS EN12266-1 Rate B.

● FEATURES

- Double flange metal seated gate valve
- Size Range:DN50-DN2000
- Standard-ISO/BS/DIN/AWWA/API
- Tests Standard-BS EN 12266-1
- Body Ring-Bronze/SS420/SS304/SS316
- Body-Ductile Iron /Cast Iron/Stainless Steel /WCB
- Fusion bonded epoxy coating-min 300 microns



RELATED PRODUCTS



SMALL DIAMETER GATE VALVE
DN50-DN300,PN10/16/25



METAL SEATED GATE VALVE
DN350-DN600,PN10/16/25



LARGE DIAMETER METAL SEATED GATE VALVE
DN700-DN2000,PN10/16/25

APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



RKS Fluid 于 1997 年在中国成立，专注于提供高质量的 CNC 加工服务。我们拥有先进的生产设备和专业的技术团队，能够满足客户在 GB、ISO、TUV for CE、ADWO-2000、TS、API 等方面的严格要求。RKS 秉承“客户至上”的经营理念，为客户提供全方位的服务。我们通过了 GB、ISO、TUV for CE、ADWO-2000、TS、API 等认证，确保产品质量和交货周期。RKS 拥有完善的质量管理体系，为客户提供从设计到生产的全方位服务。我们拥有先进的生产设备和专业的技术团队，能够满足客户在 GB、ISO、TUV for CE、ADWO-2000、TS、API 等方面的严格要求。RKS 秉承“客户至上”的经营理念，为客户提供全方位的服务。

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



