

□□ - □□□ (FB)

DN	L	□2	□	□□
40	230	139	173	3/8'''
50	230	139	173	3/8'''
65	290	159	198	3/8'''
80	310	179	226	3/8'''
100	350	214	265	1/2'''
125	400	278	307	1/2'''
150	□480□	□333□	□351□	1/2'''
200	600	600	□436□	3/4'''
250	700	□730□	□524□	1'''
300	850	850	606	1'''

□□□

1. □□□□□□□□ DN2 mm
2. □□□□□□□□□□□□
3. □□□□□□□□□□□□
4. □□□□□□□□ 64 bar □□ □□
5. □□□□FB□□□□□□RB□□□□□□□□ACD□
6. □□□□□□□□□□
- 6.1 □□□□□□1.1 * PN 1 Bar
- 6.2 □□□□□□1.5*PN1Bar
- 6.3 □□□□□□□□0.2 Bar
7. 1000 Hz □□□□□□□□□□
8. □□□□□□□□□□□□□□
9. □□□□□□□□□□□□

V TÜV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW API 6D API609

000000 00 000000000000000000000000/00/0000000000

COMPANY FACTORY



01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



Delivery



Payment



□□□□

□: □□□□□□□□□□□□□□□□

□□□□"□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

Q: 000000000000

A: RKSfluid 00000000000000000000

000000

A: 00000 2~5 00000000000000000000

Q: 00000

Q: 0000 1 00

Q: 00000000

Q: 000 100% 000002 0000000000000000

00000 TUV API WRAS CE ISO 000

0000 DIN ASME BS EN JIS API AWWA

Q: 00000000000000000000

A: RKSfluid 0020000070000000000000000000000000