

# RKSfluid®

## A key Valve in Flow Control



Butterfly Valve

Ball Valve

Gate Valve

Globe Valve

Check Valve

Pipe Fittings



- Streamlined, minimum noise
- Backflow velocity only 0.2s, Head loss 0.1bar with 2m/s
- EPDM/NBR Rubber fully coated disc
- Anti-erosion design, Self-adjusting ball
- Self-cleaning stem, Long time smooth operation

## Engineering Projects



## Partners





PTFE lined butterfly valve



Resilient seat butterfly valve



Double offset butterfly valve



Triple offset butterfly valve



Ball valve



Pipe fittings

## Our Factory



# Company Advantages



I 100% high level ex-factory inspection

II CNC precision manufacturing

III 2 professional testing centers

IV 2 years quality assurance, repair and replacement

V GB standards, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API



□□□□

□□□□□□□□□□□□□□□□□□  
□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□ RKSfluid □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
□□□□□□□□ 2~5 □□□□□□□□□□□□□□□□□□

□□ MOQ  
□□□□□□□□ 1pc □

□□□□□□□□□□□□□□□□□□  
□□□□□ 100 □□□□□□ 2 □□□□□□□□□□□□□□□□□□  
□□□□□ TUV □ API □ WRAS □ CE □ ISO □□□□  
□□□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □

□□□□□□□□□□□□□□□□□□  
□□ RKSfluid □□ 20 □□□□□□ 70 □□□□□□□□□□□□□□□□□□□□□□