






### DESIGN FEATURES



- RANGE**
- For PE and PVC pipes
  - Dimension from **32-400mm**
  - Threaded boss or flange connection
  - Female threaded boss outlets from **1/2" to 2"** or flange outlets from **DN40 to DN150**
  - Steel bolts and washers, M8, M10 or M12, A2 or AISI304

- RELIABLE**
- Saddle and strap fully **screwed tight** together

- ANTI-CORROSION**
- Thickness: **Epoxy powder** coating of **150-200µm**
  - Temperature : Spraying temperature over **200 °C**
  - Doesn't fade, even wipe with **diethyl ether**

### MATERIAL

- Epoxy powder:  , Earth Best!
- Nuts: **DACROMET®** or **GEOMET®** , Earth Best!
- Cast iron: EN-GJS-400-15 or EN-GJS-500-7, nodularity over **95%**!

### APPLICATION SCENARIO



# Our Factory



## Company Advantages

01

21 years of professional experience

03

Independent research and development team  
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂

II CNC 加工中心

III 仓库

IV 办公室

V 符合 GB 标准，TUV CE，ISO 9001，ADWO-2000，TS，PED，WRC WRAS，KTW，API 6D，API609

工厂地址：中国浙江省温州市乐清市经济开发区

## Exhibition Photos



# Our Certificates



□□□□

□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□  
 □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□  
 □□RKSfluid □□□□□□□□□□□□□□□□□□

□□□□□□□□  
 □□□□□□□□2~5□□□□□□□□□□□□□□□□□□□□□□□□

□□MOQ  
 □□□□□□□□1pc□

□□□□□□□□□□  
 □□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□□□  
 □□□□□TUV□API□WRAS□CE□ISO□□□□  
 □□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□

