DESIGN FEATURES

PE — Polyethylene
PVC — Poly Vinyl Chloride

RANGE

- For PE and PVC pipes
- Dimension from 32-400mm
- Threaded boss or flange connection
- Female threaded boss outlets from1/2" to 2" or flange outlets from DN40 to DN150
- Steel bolts and washers, M8, M10 or M12, A2 or AISI304

RELIABLE

- Saddle and strap fully screwed tight together

ANTI-CORROSION

- Thickness: Epoxy powder coating of 150-200μm
- Temperature : Spraying temperature over 200 ℃ Doesn't fade, even wipe with diethyl ether

MATERIAL

- Epoxy powder: AkzoNobel , Earth Best!
- Nuts: DACROMET® or GEOMET®, Earth Best!
- Cast iron: EN-GJS-400-15 or EN-GJS-500-7, nodularity over 95%!

APPLICATION SCENARIO

Industrial water application | Hydroelectric generation | Sewagetreatment | Water treatment | Water supply and drainage | Water transport | Pipe network in house | Irrigation

Our Factory

Company Advantages

01 21 years of professional experience

02 4 factories

03 Independent research and development team
28 top senior professional researchers

04 2 professional testing centers

05 100% high level ex-factory inspection

06 High quality imported materials

07 2 years quality assurance, repair and replacement

I□□□□□□□□□□□□□□□□□□□□□□□□

II□□CNC□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

III□□□□□□□□□□□□□□□□□□□□□□□□□□□□

IV□□□□□□□□□□□□□□□□□□□□□□□□□□□□

V□□□□□□GB□□□□□□□□□□□□□TUV CE□ISO 9001□ADWO-2000□TS□PED□WRC WRAS□KTW□API 6D□API609□

□□□/□□/□□□□□□□□□□□□□

□□□□

□□□□□□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□
□□RKSfluid□□□□□□□□□□□□□□□□□□□

□□□□□□□□
□□□□□□□□2~5□□□□□□□□□□□□□□□□□□□□□□□□

□□MOQ
□□□□□□□□□1pc□

□□□□□□□□□□□
□□□□□100□□□□□□□2□□□□□□□□□□□□□□□□□□
□□□□□TUV□API□WRAS□CE□ISO□□□
□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□□□□□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□70□□□□□□□□□□□□□□□□□□□□□□□□□□□□