



- 1□□□
2□□□□
3□□□□□□
4□□□□□

FB					
Dn	l	H2	H1	w	
40	230	139	85	173	3/8"
50	230	139	85	173	3/8"
65	290	159	95	198	3/8"
80	310	179	102	226	3/8"
100	350	214	112	265	1/2"
125	400	278	127	307	1/2"
150	480	333	145	351	1/2"
200	600	600	172	436	3/4"
250	730	730	205	524	1"
300	850	850	232	606	1 1/4"

Highlights

- 1. DN200
- 2.
- 3.
- 4. 64
- 5. FB RB ACD
- 6.
- 6.1. 1.1 * PN 1 bar
- 6.2. 1.5 * PN 1 bar
- 6.3. 0.2 bar
- 7. 1000 Hz

8

- 1
- 2.
- 24
- 24



COMPANY INFORMATION



i

ii CNC

iii

iv

v GB TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW KTW API 6D API609

VI / /



COMPANY QUALIFICATION





Partners



□□□□

□□□□□□□□□□□□□□□□
□□□□“□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□□hrdraulic□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□□□□□□□□
□□ RKSfluid □□□□□□□□□□□□□□

2⁵

□□□□
□□□□□□□1□□

[illegible]

TUV API WRAS CE ISO
DIN ASME BS EN JIS API AWWA

RKSfluid 27 70