

PRODUCT STRUCTURE

Features

- Size range DN100-1200mm
- Standard-ISO/ BS/DIN /AWWA/API
- Tests standard-BS EN 12266-1
- Body-Ductile Iron/Cast Iron/Stainless Steel/WCB
- Body Ring-SS420/SS304/SS316
- Disc Ring-EPDM
- Shaft-420/S5431/SS316
- Fusion bonded epoxy coating- Min 300 Microns

This series tilting check valves are suitable to be used at the exit of the pump whose medium is water. It is used to prevent or reduce medium back from water hammer. So it can protect the pipeline system. Suitable temperature $\leq 80^{\circ}\text{C}$



APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



COMPANY FACTORY



COMPANY INFORMATION



i 工厂内所有设备均符合 ISO 9001 标准

ii CNC 加工中心均符合 ISO 9001 标准

iii 所有设备均符合 ISO 9001 标准

iv 所有设备均符合 ISO 9001 标准

v 工厂符合 GB 15576-2015 TUV CE ISO 9001 ADWO-2000 TS PED WRC WRAS KTW KTW API 6D API609

VI 工厂所有设备均符合 ISO 9001 / CE / PED 标准

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06

COMPANY QUALIFICATION



COMPANY EXHIBITION



0000

00000000000000000000000000
000000000000000000000000000

00000000000000000000000000
00000000hrdraulic000000 RKSfluid000000000000000000000000000000

00000000000000000000000000
00RKSfluid00000000000000000000

0000000000
0000000020500000000000000000000000000000

000
00000000100

00000000000000000000000000
0000001000000002000
000000TUV00API00WRAS00CE00ISO0000
000000DIN00ASME00BS EN00JIS00API00AWWA0

00000000000000000000000000
00RKSfluid0020000000000000007000