



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport



# COMPANY FACTORY



# COMPANY INFORMATION



i 工厂生产的产品符合 ISO 9001 标准

ii 工厂 CNC 加工精度符合 ISO 10012 标准

iii 工厂生产的产品符合 ISO 14001 标准

iv 工厂生产的产品符合 ISO 45001 标准

v 工厂符合 GB 15490 标准，TUV CE，ISO 9001，ADWO-2000，TS，PED，WRC，WRAS，KTW，KTW，API 6D，API609

vi 工厂符合 GB 15490 标准，TUV CE，ISO 9001，ADWO-2000，TS，PED，WRC，WRAS，KTW，KTW，API 6D，API609



## COMPANY QUALIFICATION





