



- Better sealing effect, prevent leakage
- Easier replace the filter bag, lower operating cost
- Adjustable installation height to meet specific application occasions
- Large effective filtration area and higher filtration efficiency
- Longer filter bag service life
- Reasonable structure, more stable and reliable filtration
- China GB-150, International ASME, CE Pressure Standards



- Suitable for high capacity & large flow filtration
- Provided 3 ~ 24 bags design structure
- Equipped with standard size flange
- Flow from 120 to 960 cubic/hours
- Excellent welding quality, safe and reliable

Our Factory



Company Advantages



1. 100% high level ex-factory inspection
2. 21 years of professional experience
3. API, AWWA, ASME, BS, EN, DIN, JIS, TUV, CE, ISO9001, TS, OHSAS, WRAS
4. 2 years quality assurance, repair and replacement

Exhibition Photos



Our Certificates





Tel: 024 2318 0188-899

Email/Skype: ivory@rksfluid.com

Mobile/WhatsApp/Wechat: +86 15140071761

Add: Pump & Valve Industrial Park, No. 5 Panwu Road,
Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□
 □□1□□□□□□□□
 A1□□□□□□□□□□□□□□□□

Q2□□□□□□□□□□
 A2□□□□□□5-10□□□□□□□□□□□□□□□□15-90□□

□□3□□□□□□□□
 A3□T / T 30□□□□□□□□□□□□□□□□□□□□□□

□□4□□□□□□□□□□□□□□□□□□□□□□

A4 1

Q5

A5 100

Q6

A6

7

A7 1