



DESIGN FEATURES

VERSATILE & RANGE

- Up to 28mm of tolerance, **DN40 ~ DN450** stock reduction
- Allows angular deflection of **+/-3°** per gasket
- Covering most common pipe materials



OPTIMAL SEALING

- **Unique gasket** with circumferential ribs sealing on corroded, scored or pitted pipes

DURABLE

- **ANTI-CORROSION**
- Thickness: **Epoxy powder coating of 200-250µm**
- Temperature : **Spraying temperature over 200°C**
Doesn't fade, even wipe with **diethyl ether**

MATERIAL

- Epoxy powder: **AkzoNobel**, Earth Best!
- Nuts: **DACROMET®** or **GEOMET®**, Earth Best!
- Cast iron: **EN-GJS-500-7**, nodularity over **95%**!
- Flange Adaptors: for most common flange standards. **PN10/16/ANSI150** drilled

APPLICATION SCENARIO



Our Factory



Company Advantages

01

21 years of professional experience

03

Independent research and development team
28 top senior professional researchers

05

100% high level ex-factory inspection

07

2 years quality assurance, repair and replacement

4 factories

02

2 professional testing centers

04

High quality imported materials

06



I 工厂

II CNC 加工中心

III 仓库

IV 办公室

V 认证 GB, TUV CE, ISO 9001, ADWO-2000, TS, PED, WRC, WRAS, KTW, API 6D, API609

工厂地址: 中国浙江省温州市乐清市经济开发区

Exhibition Photos



Our Certificates



□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□

□□□□□□□□□□
 □□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□
 □□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□□□
 □□□□□□□□ 2015 □□□□□□□□□□□□□□□□□□□□□□

□□□□□□
 □□□□□□□□ 1pc □

□□□□□□□□□□
 □□□□□□□□ 100 □□□□□□□□ 2 □□□□□□□□□□□□□□□□
 □□□□□□□□ TUV □ API □ WRAS □ CE □ ISO □□□□
 □□□□□□□□ DIN □ ASME □ BS EN □ JIS □ API □ AWWA □

□□□□□□□□□□□□□□□□

□□RKSfluid□□20□□□□□□70□□□□□□□□□□□□□□□□□□□□
□□□□□□PVC□□□□□□