



RK fluid®

A key Valve in Flow Control



Product Description



Super Anti-corrosion
Epoxy powder coating **200-250µm**,
baking varnish over **200°C**,
use  material.



Free wedge nut, **reduces the stem bending forces** and at the same time enables it to be easily replaced.



The more compact new cap, reduces the water retention areas in order to **reduce the risk of bacterial growth**.



One piece stainless steel stem in for **better resistance to axial load and to with stand higher operating torques**.



Three locking tab for bayonet system prevents self-dismantling.



Dust guard integrating three O-ring shape, **prohibiting the introduction of foreign bodies** at the stem.



Male guiding system with composite sliding skate reduces the wear of the wedge against the body, allowing a smooth functionality and a longer life time of the valve.



Triple seal at the operating stem to ensure tightness with the test of time (2500 cycles).



New male composite sliding skate technology ensuring a low operating torque even under high differential pressure and preventing damage or corrosion generated by the friction.

Engineering Projects



Product Category







I 00000000000000000000

II 000CNC00000000000000000000000000000000

III 00000000000000000000000000000000000000

IV 00000000000000000000000000000000000000

V 00000GB0000000000000TUV CE00ISO 900100ADWO-200000TS00PED00WRC WRAS00KTW00API 6D00API60900

XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX/XX/XXXXXXXXXXXXXXXX

Our Factory



Exhibition Photos



Our Certificates



□□□□

□□□□□□□□□□□□□□□□
 □□□□□□□□□□□□□□□□

□□□□□□□□□□

RKSfluid

RKSfluid

25

1pc

100 2

TUV API WRAS CE ISO

DIN ASME BS EN JIS API AWWA

RKSfluid 20 70