



## DESIGN FEATURES

### DURABLE

- No-pin connection, 1 pc blow-out proof stem
- DI/CI Nodularity over 95%

### ANTI-CORROSION

- Material: Epoxy powder:  Earth Best!
- Coating Thickness: 200-250µm
- Spraying temp: over 200°C. Doesn't fade, even wipe with diethyl ether

### QUALITY STANDARD

- 100% quality test, follow DIN, ASTM, JIS, GB/T, ISO, BS EN, API
- ONLY ONE Manufacturer get CE certification up to DN1800
- 2 years warranty. 15000 times On-off test, 30000 times Destructive experiment



# APPLICATION SCENARIO



Industrial water application



Power plant



Sea water desalination



Water treatment



Water supply and drainage



HAVC



Food and drug



Water transport





# COMPANY FACTORY



# COMPANY INFORMATION



i 工厂生产的产品符合以下标准

ii CNC 加工的产品符合以下标准

iii 工厂生产的产品符合以下标准

iv 工厂生产的产品符合以下标准

v 工厂符合 GB 标准，并通过了 TUV CE、ISO 9001、ADWO-2000、TS、PED、WRC、WRAS、KTW、KTW、API 6D、API609 认证

vi 工厂符合 [ISO 14001](#) 标准，并通过了 / 认证





## COMPANY QUALIFICATION



# COMPANY EXHIBITION



□□□□□

□□□□□□□□□□□□□□□□□□  
 □□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
 □□□□□□□hrdraulic□□□□□□ RKSfluid□□□□□□□□□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
 □□RKSfluid□□□□□□□□□□□□□□

□□□□□□□□□□□□□□□□□□  
 □□□□□□□2□5□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□□□  
 □□□□□□□□1□□

□□□□□□□□□□□□□□□□□□  
 □□□□□100□□□□□□□□2□□□□□□□□□□□□□□□□□□□□□□□□□□  
 □□□□□TUV□API□WRAS□CE□ISO□□□□□□□□□□□□□□□□□□□□□□□□□□□□  
 □□□□□DIN□ASME□BS EN□JIS□API□AWWA□

□□□  
 □□RKSfluid□□20□□□□□□□□□□70□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

