



- Better sealing effect, prevent leakage
- Easier replace the filter bag, lower operating cost
- Adjustable installation height to meet specific application occasions
- Large effective filtration area and higher filtration efficiency
- Longer filter bag service life
- Reasonable structure, more stable and reliable filtration
- China GB-150, International ASME, CE Pressure Standards



- Filter different chemical **acid** and **alkali** liquids
- No seam, no dead angle, precise specification
- Smooth surface, no groove, no dead angle, easy to clean
- Can withstand **high temperature** and **high pressure**
- High quality, high efficiency, economical & practical





- Suitable for high capacity & large flow filtration
- Provided 3 ~ 24 bags design structure
- Equipped with standard size flange
- Flow from 120 to 960 cubic/hours
- Excellent welding quality, safe and reliable

## Our Factory



## Company Advantages



1. 21 years of professional experience
2. 4 factories
3. Independent research and development team  
28 top senior professional researchers
4. 2 professional testing centers
5. 100% high level ex-factory inspection
6. High quality imported materials
7. 2 years quality assurance, repair and replacement



## Exhibition Photos



## Our Certificates





Tel: 024 2318 0188-899  
 Email/Skype: ivory@rksfluid.com  
 Mobile/WhatsApp/Wechat: +86 15140071761  
 Add: Pump & Valve Industrial Park, No. 5 Panwu Road,  
 Liaozhong Dist. Shenyang, Liaoning P.R. China

□□□□

Q1□□□□□□□□□□

A1□□□□□□□□□□□□□□

Q2□□□□□□□□

A2□□□□□5-10□□□□□□□□□□□□□□15-90□□

□□3□□□□□□□□

A3□T / T 30□□□□□□□□□□□□□□□□□□□□□□□□

Q4□□□□□□□□□□□□□□□□□□

A4 1pc

Q5

A5 100

Q6

A6

Q7

A7 1