1、单室截止型主阀；
2. 球墨铸铁**EN-GJS-500-7**阀体和阀盖；
3、**CF8/SUS304**阀座、轴；
4、**EPDM**垫片和隔膜；
5。瓦**RAS** 环氧粉末涂料；
6.PN10/16/25

主阀 - 全通径 **(FB)**					
DN	L	氢2	H1	W	港口
40	230	139	85	173	3/8"
50	230	139	85	173	3/8"
65	290	159	95	198	3/8"
80	310	179	102	226	3/8"
100	350	214	112	265	1/2"
125	400	278	127	307	1/2"
150	第480章	第333章	145	第351章	1/2"
200	600	600	172	第436章	3/4"
250	第第第730章章章	730	205	第524章	1"
300	850	850	第232章	606	1"

亮点

1. 全通径，阀座直径为 DN2 mm
2.即使流量接近零也能稳定工作
3. 高性能、高强度尼龙加强膜片
4.一百万次循环测试和64巴爆破测试
5. 全通径（FB）、缩径（RB）和防气蚀装置（ACD）
6.高于标准产品测试，
6.1 阀座测试：1.1 * PN 1 Bar
6.2 强度测试：1.5*PN1Bar
6.3 低压密封试验：0.2 Bar
7. 1000 Hz 传感器自动电脑测试
8、智能控制阀及解决方案系统

为什么选择我们

1.我们提供最具竞争力的解决方案、最专业的技术支持、最全面的质量管理和最优质的客户服务。
2、我们承诺：
产品保修期：24个月。
回复：每天24小时在线

COMPANY FACTORY

COMPANY INFORMATION

I[illegible]

Ⅱ [illegible]

Ⅲ[illegible]

[illegible]

V [illegible]TUV CE[illegible]ISO 9001[illegible]ADWO-2000[illegible]TS[illegible]PED[illegible]WRC WRAS[illegible]KTW[illegible]API 6D[illegible]API609[illegible]

[illegible]/[illegible]/[illegible]

COMPANY QUALIFICATION

COMPANY EXHIBITION

[illegible]

[illegible]: [illegible]
[illegible]”[illegible]

[illegible]: [illegible]
[illegible] RKSfluid [illegible]

[illegible]: [illegible]
A[illegible] RKSfluid [illegible]

[illegible]
A[illegible] 2~5 [illegible]

[illegible]: [illegible]
[illegible]: [illegible] 1 [illegible]

[illegible]: [illegible]
[illegible]: [illegible] 100% [illegible]2 [illegible]
[illegible] TUV[illegible]API[illegible]WRAS[illegible]CE[illegible]ISO [illegible]
[illegible] DIN[illegible]ASME[illegible]BS EN[illegible]JIS[illegible]API[illegible]AWWA[illegible]

[illegible]: [illegible]
A[illegible] RKSfluid [illegible]20[illegible]70[illegible]