

FB - FB (FB)					
DN	L	2	H1		
40	230	139	85	173	3/8"
50	230	139	85	173	3/8"
65	290	159	95	198	3/8"
80	310	179	102	226	3/8"
100	350	214	112	265	1/2"
125	400	278	127	307	1/2"
150	480	333	145	351	1/2"
200	600	600	172	436	3/4"
250	730	730	205	524	1"
300	850	850	232	606	1"

1. DN2 mm
- 2.
- 3.
- 4.64
- 5.(FB)(RB)(ACD)
- 6.
- 6.1 1.1 * PN 1 Bar
- 6.2 1.5*PN1Bar
- 6.3 0.2 Bar
7. 1000 Hz
- 8.

- 1.
 - 2.
- 24
- 24





COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□

□: □□□□□□□□□□□□□□□□
□□□□”□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□
A□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□□□□□□□
A□ □□□□□ 2~5 □□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□□

□: □□□□□□
□: □□□□ 1 □□

□: □□□□□□□□□□
□: □□□ 100% □□□□□□2 □□□□□□□□□□□□□□□□□□□□□□□□
□□□□□ TUV□API□WRAS□CE□ISO □□□□
□□□□□ DIN□ASME□BS EN□JIS□API□AWWA□

Q: 如何選擇合適的液體？

A: RKSfluid 27000 液體適用於大多數的應用。