

[illegible]

Reliability Keeps Safety



1. □□
2. □□
3. □□
4. □□□□□
5. □□
6. □□□

- 1. □□
2. □□□□
3. □□□□□
4. □□□□

FB - FB (FB)					
DN	L	2	H1		
40	230	139	85	173	3/8"
50	230	139	85	173	3/8"
65	290	159	95	198	3/8"
80	310	179	102	226	3/8"
100	350	214	112	265	1/2"
125	400	278	127	307	1/2"
150	480	333	145	351	1/2"
200	600	600	172	436	3/4"
250	730	730	205	524	1"
300	850	850	232	606	1"

FB

1. DN2 mm
- 2.
- 3.
- 4.64
5. FB RB ACD
- 6.
- 6.1 1.1 * PN 1 Bar
- 6.2 1.5*PN1Bar
- 6.3 0.2 Bar
7. 1000 Hz
- 8.

FB

- 1.
 - 2.
- 24
- 24



COMPANY QUALIFICATION



COMPANY EXHIBITION



Partners



□□□□

□: □□□□□□□□□□□□□□□□
□□□□"□□□□□□□□□□□□□□□□

□: □□□□□□□□□□□□□□□□
□□□□□□□□□□□□□□ RKSfluid □□□□□□□□□□□□□□□□□□□□

□: □□□□□□□□□□
A□ RKSfluid □□□□□□□□□□□□□□□□

□□□□□□
A□ □□□□□ 2~5 □□□□□□□□□□□□□□□□□□□□

□: □□□□□□
□: □□□□ 1 □□

□: □□□□□□□□□□
□: □□□ 100% □□□□□□2 □□□□□□□□□□□□□□□□□□□
□□□□□ TUV□API□WRAS□CE□ISO □□□□
□□□□□ DIN□ASME□BS EN□JIS□API□AWWA□

Q: 如何選擇合適的液體？

A: RKSfluid 27000 液體適用於大多數的應用，但對於某些特殊的應用，可能需要選擇其他的液體。